
T SERIES CAPLUGS (NON-THREADED)






Tapered Caplugs can be used as either caps or plugs. Because they are tapered in design and made from highly pliable (or flexible) Polyethylene, they can be applied to fit snugly and are readily removable, whether used for capping or plugging. Especially recommended for use on MIL Std. and SAE-type tube and hydraulic fittings and for threaded external and internal NPT fittings.

Part No.	Dash No.	Tubing O.D.	Thread	Caplugs As Plugs	Caplugs As Caps	Price Each	
04-00045	-2	1/8	5/16-24	1	2		
04-00046	-3	3/16	3/8-24	2	3-X		
04-00047	-4	1/4	7/16-20	3	4-X		
04-00048	-5	5/16	1/2-20	4	5		
04-00049	-6	3/8	9/16-18	5	6-X		
04-00050	-8	1/2	3/4-16	8	9-X		
04-00051	-10	5/8	7/8-14	10	11-X		
04-00052	-12	3/4	1 1/16-12	12-X	13-X		
04-00053	-16	1	1 5/16-12	14-X	15-X		

Less 20% Discount on 50 Caplugs (Same P/N)

SC SERIES CAPLUGS (NON-THREADED)






Series SC sleeve caps are designed to fit outside diameters of tubing sizes listed with a snug friction grip. Available in 57 different O.D.'s and lengths. Ideal for capping and protecting both threaded and nonthreaded tubing or rod ends. The also make excellent masks, for painting, plating or grit-blasting operations.

Less 20% Discount on 50 Caplugs (Same P/N)

			A	E		
Part No.	Caplug No.	To fit to	ube O.D.	Insidel	Price Ea.	
		Inches	mm	Inches	mm	
04-00054	SC-1/8	1/8	3.18	.59	14.99	
04-00055	SC-3/16-5	3/16	4.76	.35	8.89	
04-00056	SC-3/16-16	3/16	4.76	1.00	25.40	
04-00057	SC-1/4-4	1/4	6.35	.22	5.59	
04-00058	SC-1/4-14	1/4	6.35	.88	22.35	
04-00059	SC-5/16	5/16	7.94	.88	22.35	
04-00060	SC-3/8	3/8	9.53	.88	22.35	
04-00061	SC-7/16-14	7/16	11.11	.88	22.35	
04-00062	SC-1/2-8	1/2	12.70	.50	12.70	
04-00063	SC-1/2-14	1/2	12.70	.88	22.35	
04-00064	SC-9/16-9	9/16	14.29	.56	14.22	
04-00065	SC-9/16-14	9/16	14.29	.88	22.35	
04-00066	SC-5/8	5/8	15.88	.88	22.35	
04-00067	SC-3/4	3/4	19.05	.88	22.35	
04-00068	SC-7/8	7/8	22.23	.88	22.35	
04-00069	SC-1	1	25.40	1.00	25.40	

CD SERIES CAPLUGS (THREADED)






Knurled for ease of application, Series CD caps seal flared JIC fittings exceptionally well against dirt and moisture, as well as for masking during dipping, painting and plating.

		To Cap			im			
Part No.	Caplug No.	Normal Tubing Size Inches	To fit		Α	No. of	Price	
			Thread	In	mm	Knurls	Each	
04-00032	CD-3	3/16	3/8-24	.47	11.94	4		
04-00033	CD-4	1/4	7/16-20	.47	11.94	4		
04-00034	CD-5	5/16	1/2-20	.47	11.94	6		
04-00035	CD-6	3/8	9/16-18	.53	13.46	6		
04-00036	CD-6A	3/8	5/8-18	.53	13.46	6		
04-00037	CD-8	1/2	3/4-16	.57	14.48	6		
04-00038	CD-10	5/8	7/8-14	.68	17.27	6		
04-00039	CD-11	_	1-14	.78	19.81	8		
04-00040	CD-12	3/4	1 1/16-12	.75	19.05	8		

Less 20% Discount on 50 Caplugs (Same P/N)

PD SERIES CAPLUGS (THREADED)





Series PD Plugs, designed for use on flared JIC fittings, air knurled for ease of application. They will seal low pressure requirements with light finger tightening. PD plugs can be used to seal 37° flare fittings without gaskets.

	Caplug	To Plug Nominal	To fit	Dimensions						
Part				В		С		D		Price
No.	No.	Tubing Size	Thread	in	mm	in	mm	in	mm	Each
04-00023	PD-30	3/16	3/8-24	.46	11.68	.50	12.70	.18	4.57	
04-00024	PD-40	1/4	7/16-20	.53	13.46	.62	15.75	.19	4.83	
04-00025	PD-50	5/16	1/2-20	.53	13.46	.68	17.27	.25	6.35	
04-00026	PD-60	3/8	9/16-18	.50	12.70	.81	20.57	.25	6.35	
04-00027	PD-65	3/8	5/8-18	.59	14.99	.81	20.57	.25	6.35	L
04-00028	PD-80	1/2	3/4-16	.75	19.05	.94	23.88	.25	6.35	
04-00029	PD-100	5/8	7/8-14	.87	22.10	1.06	26.93	.25	6.35	
04-00030	PD-121	3/4	1-1/16-14	1.12	28.45	1.31	33.28	.25	6.35	
04-00031	PD-160	1	1-5/16-12	.93	23.62	1.50	38.10	.25	6.35	L

Less 20% Discount on 50 Caplugs (Same P/N)