# **FUEL TANKS**




#### **FUEL WARNING SYSTEM**

Float-action sensor in tank activates panel warning light when fuel supply is low. All-PBT unit, impervious to aviation fuel. Use AN 867-4 flange for mounting.

Sensor......P/N 6905-400 ..... Warning Light.....P/N 05-17660 ..... Bulb(GE-330) .....P/N 11-04016 .....

DISCOUNTS: 10% ON 6, 15% ON 12, 20% ON 50

### **INVERTED PICKUP TUBES**



pipe thread attached to tank outlet. Available for any of the tanks listed, or others. Specify tank model and tube length. Minimum length available is 9"

9" P/N 05-205	09 10	"P/N 0	5-20510
11" P/N 05-205	11 12	"P/N 0	5-20512
13" P/N 05-205	13		

# Add \$1.80 to 13" price for each additional inch. PICKUP TUBE ADAPTER

Specially machined AN912 fitting for connecting pickup tube to fuel tank.

## FLOP TUBE ADAPTER WITH SIDE OUTLET

# **ALUMINUM WELDING FLANGES**



	Part No.	Female Pipe Thread	Dia. "D" In	Height "H" In	Price Each
١	AN867-1		1-1/2	7/16	
١	AN867-2	1/4"	1-3/4	5/8	
١	AN867-3	3/8"	1-7/8	5/8	
١	AN867-4	1/2"	2	3/4	
١	AN867-6	3/4"	2-1/4	13/16	
Į	AN867-8	1"	2-11/16"	1"	

# FINGER STRAINERS

Finger strainers are strainers for fuel tank outlets. Standard size features a brass fitting with 3/8" male pipe thread which fits AN867-3 welding flange, and 1/4" female pipe thread for valve or fuel line fitting. Screen is 16 mesh brass. Large finger strainer has a 3/8"-NPT x 1/2"-M-NPT brass

bushing with a T304 stainless steel screen.

Standard .... P/N 05-17700...... Large .... P/N 05-04445 .....



### RAVEN HEADER TANKS

Header tank used for any aerobatic aircraft such as Pitts Specials etc. Comes with mounts to attach to existing tank straps, clamps and weld-in fitting for main tank. 16" x 7" in diameter. Holds approximately 2-1/2 gallons. Weighs 3 lbs.

P/N 05-00913 .....



### **RAVEN WING TANKS**

Wing tank used to hold extra fuel or smoke oil in top wing of aerobatic biplanes.

S1-S Wing Tank	P/N 05-00914
	P/N 05-00915
Experimental S2, Eagle Wing	TankP/N 05-00916

# **FUEL TANK DRAIN FITTING**



This specially designed fuel tank drain fitting minimizes drain flow vortexing that allows water and contaminants to remain in tank no matter how many times the drain cycle is repeated. Threads are 1/8" NPT - brass throughout P/N 05-28900 ......

### **ULTRALIGHT FUEL TANKS**



### **ULTRALIGHT 12-1A FUEL STRUT TANK**



# ULTRALIGHT BVR 2-1K COMPLETE TANK KIT

2 tanks and hardware for Beaver RX550. P/N 05-03066 .....



#### ULTRALIGHT CHI 12-1K COMPLETE TANK KIT

2 tanks with hardware for chinook

P/N 05-03067 .....



PITTS SPECIAL FUEL TANK

# **OPTIONAL TANK INSTALLATIONS**

Sight Gauge (Fittings and Tubing) for Pitts o Skybolt Tanks - no installation charge. P/N 05-29000.....

Flop Tube, Low Fuel Level Warning, Flusl Filler Cap (specify type) - Add \$5.00 installation charge and cost of unit to price of tank.

**ELECTRIC SENDER** - Add \$15.00 installatio charge and cost of unit to price of tank.

#### FUEL TANK HOLD DOWN STRAPS

Fabricated from.035 stainless steel. Straps are 1"wide x 36" long. For VariViggen Starduster & others. P/N 05-20400......

# ANTI-CHAFE CHANNEL FOR FUEL TANK STRAPS

Neoprene rubber extrusions to hold 1" wide metal fuel tank straps.

#9 Channel P/N 05-01800 ..... . Ft.

# ALUMINUM FUEL TANKS

	712011111011111111111111111111111111111							
	Design	Capacity (Gallons)	Main Tank	Part No.	Tank for Inverted Flight	Part No.	Each Wing Tank	Part No.
	Acro-Sport II	24				05-18510		
	Baby Greatlakes	10		05-03058				
	Cougar	23		05-18600				
	Cuby	12.5		05-18700				
	EAA Bi-Plane	16		05-18800				
	Fly Baby	14		05-18900				
	Hatz Bi-Plane	18						05-19020
or	Mustang I	16		05-19100				
-	Mustang II	27		05-19200				
	Pitts Special	19				05-19310		
sh	Pober Pixie	12	(Send Drwg.	05-19400)				05-19420
la-	Skybolt	29		_		05-19510		05-19520
ıa-	Smith Miniplane	16		05-19600				
	Starduster I	18		05-19700		05-19710		05-19720
on	Starduster II	26		05-19800		05-19810		05-19820
	Tailwind			05-19950				

SEE PRO-SEAL TANK SEALANT AND SLOSHING COMPONENTS IN COVERING SUPPLIES SECTION

**CAUTION:** Electric sender should not be installed in a tank with flop tube to prevent possible entanglement. Tank should be free of everything but flop tube. Use sight gauge with flop tube. Prices are based on tanks manufactured to the original plans as issued by the designer. Minor modifications such as changes in tank fitting sizes or locations can be made at additional charge. Please submit all pertinent data with respect to desired changes at time of order.

ALLOW 2-3 WEEKS DELIVERY TIME ON ALL TANKS.