CK CORD S - RI



MILL FRESH SHOCK RINGS

An endless elastic ring composed of multiple strands of natural rubber, wound into a circular skein. Braided cover is high grade yarn. Manufactured to meet specification MIL-C-5651B, Type II. Shock cord is used in landing gear to

reduce shock transmitted to fuselage while landing and taxiing and on other shock mounting applications. Color coded to insure fresh stock.

Ring No.	Ring Size* (In.)	Test (Lb.)		# Req.	Part No.	Price Ea.
9044	9/16x4-1/2	400	Hatz Bi-Plane	4	9044	
9090	9/16x9	425	Taylorcraft B	4	9090	
9010HD	9/16x10	475	Taylorcraft BC	4	06-00829	
9010HDX	9/16" X 10"		Taylorcraft F-19/F-21	4	06-01132	
1080	5/8x8	750	Stolp Starduster.Rans S4/5	4	1080	
1080HD	5/8x8	900	PA-16. PA-18	4	06-00823	
			PA-20. PA-22. PA-25	4		
1174	11/16x7-1/2	730	Piper J-2. Early J-3. J-5	4	06-00756	
1192	11/16x9-1/4	750	Taylorcraft D	4	1192	
11104	11/16x10-1/2	750	Taylorcraft L-2	4	11104	
1280	3/4x8	750	Stolp Starduster Too	4	1280	
1280-HD	3/4x8	950	Piper J-3 (S/N8277 up).	4	06-00826	
			PA-11. PA-12. PA-14	4		
			PA-18 (thru S/N18-3013)Rans	4		
			S10 Acrosport, Pitts S-2			
8097	1-1/2 x 9-7/8	400	PA-24. PA-30	2	8097	
1286	3/4x8-3/4	750	Aeronca (S/N330 up)	4	1286	
1286HD	3/4x8-3/4	950	Skybolt	6	06-00827	
1380	13/16x8	1160	PA-20 (before 1952)	4	1380	

*1st dimension is cross section; 2nd dimension is inside dia. of ring. HD - Heavy Duty, higher test rings. ***6 Rings for J-5. HDX - Extra Heavy Duty.

CW (Cold Weather) shock rings available on Special Order basis. Prices are approx. twice that of standard shock rings. Add "-CW" to standard part number when ordering.

SHOCK CORD

Made of fine natural rubber thread encased in a jacket of 2-ply woven cotton cord. Rubber strands are pre-stretched for an ultimate elongation of 120 to 140%. Treated to resist wear and oxidation. Meets specification MIL-C-5651B.

				TPE I			
Dia. (In.)	Part No.	Price/Ft. Less Than 100 Ft.	100 Ft.	Dia. (In.)	Part No.	Price/Ft. Less Than 100 Ft.	100 Ft
1/8	06-12100			1/2	06-12500		
1/4	06-12200			5/8	06-12600		
5/16	06-12300						
3/8	06-12400						

SHOCK CORD FASTENERS

These cone spring hooks and locking rings are used as terminal fasteners. Insert cord through small end of cone. Apply and crimp locking ring about 1/2" from end of cord, pull cord back until locking ring contacts inside of fastener. Cut ends of cord may be sealed by dipping in rubber

cement. Set includes	Snock Cord Size	Fastener P/N	Price/Set
cord and locking ring.	1/4"	06-12800	
2 Times	3/8"	06-12900	
m m m m m m	1/2"	06-13000	l

SHOCK CORD INSTALLATION TOOL

This handy new tool installs standard shock rings on most aircraft without the great effort required in the past. This tool is designed for use with the shock cords shown above. Our price is the best anywhere. P/N 06-16600.....

BOGERT COMANCHE BUNGEE TOOL

 Lower damage risk with the right tool
Complete control of bungee shock cords coming off
Complete control of bungee shock cords going on. • E-Z instructions with detailed drawings · Safe landings depend on new cords every few years. P/N 06-00419.....

BOGERT COMANCHE GEAR

RETRACTION TOOLS

Straight - Fits: PA-24, SN 24-1 through 24-4782 & 24-4784 through 24-4803 P/N 12-02095..... **Angled -** Fits: All PA-30's, PA24, Serial number 24-4783, 24-4804 & up P/N 12-02094...... 4783, 24-4804 & up



BUNGEE-MASTER

At last... a tool that takes the hassle out of shock cord installation. Bungee-Master is quick, easy, and safe. A one man operation. It is small and compact, and fea-

tures all metal construction with black anodized finish. Shock cords are stretched evenly with Bungee-Master using easy bench top operation. Requires only a shop vise. Will install shock cords on J-3 Cub, PA-18 Super Cub, PA-20 Pacer, PA-22 Tri-Pacer, PA-22 Colt, and the PA-25 P/N 06-03910 Pawnee



SHOCK ABSORBER COIL RINGS

High pressure springs fabricated from alloy steel for

Discount 10% on 6, 15% on 12



GRANVILLE'S STRUT SEAL

Landing gear strut packing seals shrink due to fluctuating weather conditions and age. This specially engineered hydraulic chemical additive leaves a protective coating on the strut shaft and allows the seal to expand to its normal size. It will stop strut leaks and is an excellent lubricant and corrosion preventative. Application is fast and easy - any owner or pilot can do the job in minutes. FAA approved.

Single-Strut Kit	P/N 06-13300
3-Strut Kit (Single Engine)	
3-Strut Kit (Medium Twins)	
Large Twin kit (16 oz0	
Granville Strut Additive (Pt.)	

STRUT REBUILD KITS FOR CESSNA NOSE STRUTS

For Cessna models 150, 152, 172, 175, 182, R182, 205, 206, 210, T210, P210, 310-310Q, 320, 336, & 337. Includes 5 O-Rings, 2 Back-Up

FOR PIPER NOSE STRUTS

For Piper PA28-140, 150, 151, 160, 161, 180, 181, & 235, PA32-260 & 300. Includes O-Rings, Back-Up Ring, Seal, Wiper & Aluminum

For Piper PA28R & PA32R series retractable nose struts. Includes Seals, O-Rings & Gasket. P/N 06-03970

FOR PIPER MAIN STRUTS

For Piper PA28-140, 150, 151, 160, 161, 180, 181 & 235, PA32-260 & 300. Includes O-Rings, Scraper, Seal & Aluminum Gasket.

P/N 06-03975

For Piper PA28R & PA32R series retractable main struts, Includes Seals, O-Rings & Gasket. P/N 06-03980



STRUT SEAL KITS FOR PIPER Kits contain Mil-Spec & Industry Standard Seals

and Components required for various Piper Strut application Seal kit for nose or main strut for Piper Apache/

		Aztec		06-0012	ნ	
Strut seal k	it for Piper	PA-24 main g	ear	06-0012	7	
Strut seal k	it for Piper	PA24 nose ge	ear	06-0012	8	
Strut seal k	it for Piper	PA30 main ge	ear	06-0012	9	
Strut seal k	it for Piper	PA30 nose ge	ear	06-0013	0	
Main Strut	seal kit for	Piper PA28 14	40, 150, 1	51, 160,	161, 180,	,
181, 235,	& PA32-2	60, 300		06-0397	5	
Nose strut:	seal kit for	PA28-140, 15	0, 151, 16	0, 161,1	80, 181, 2	235, &
PA32-260), 300			06-0396	5	
Main strut s	seal kit for l	PA28R & PA32	2R-300, 3	01, 301T	, & PA32	RT-300,
300T				06-0398	0	
Nose strut:	seal kit for	PA28R & PA3	32R-300, 3	301, 301	T, &	
PA32RT-3	300			06-0397	0	

HOMEBUILT AIRCRAFT LANDING GEAR

These custom landing gear are fabricated from aircraft grade 2024T3 aluminum. After cutting and milling, they are annealed to "O" condition for bending, and then heat-treated to "T6" condition for exceptional strength and durability. Top quality landing gear at exceptional pricing.



NOTE:Request landing gear lavout sheet when placing order or quotation Request for custom landing gear to verify correct gear for application.

Aircraft Type	Part No.	Price
KITFOX - Mod 3&4 TD	06-04025	
PITTS - S1	06-03915	
S1-11B SuperStinker	06-04035	
Baby Lakes	06-04070	
VP1 - 1100B Free Standing No Cables	06-04040	
Zenair CH701	06-00058	

NOTE:

ALL GROVE AIRCRAFT LANDING GEAR IS NON-CANCELLABLE / NON-RETURNABLE.