JNTERSINK CUT



MICROSTOP COUNTERSINK **CUTTER KIT AT590CSK**

This kit provides countersinking versatility with nine different 1/2" diameter cutters, six of the most commonly used foot pieces, and a high-speed bearing-constructed microstop. The microstop controls cutting depth in .001 increments, from 0 to 5/16". Cutters-ground on-centers to ensure #30, #21, 3/32", 1/8", 3/16", and 1/4". P/N 12-00824.....

100° AT455 COUNTERSINK CUTTER

Designed for operating in angle drills with 1/4-28 threads and in the AT441SLS Micro Stop Countersink. Has 1/4-28 threaded shank. Cutter angle 100°. AT455D-4 has 7/16" dia. cutter head. Use with AT484 pilots. P/N AT455D-4

(A	
<u>(</u>	ر 1.086 dia.

AT484 PILOTS have a .086" dia. shank with a flat to accommodate the set screw of the AT455 cutter. An undercut permits the head to seat on the cutter angle. Order by P/N..... ea.

Part No.	Head Dia. "D"	Part No.	Head Dia. "D"
AT484-2	#40	AT484-56	3/32
AT484-12	#30	AT484-57	1/8
AT484-21	#21	AT484-59	5/32
AT484-31	#11	AT484-61	3/16
AT484-32	#10	AT484-63	7/32

AT441 HSS MICROSTOP COUNTERSINK



AT441 HS Micro Stop Countersink, similar to the AT442SLS unit, except with 1/4-28 female threaded nose to accommodate AT455 cutter. P/N 12-01591.....

AT 442 HS MICRO STOP COUNTERSINK



A precision tool for production countersinking. Ball thrust bearing for absolute depth control. Adjusts in .001" increments, with positive adjustment lock. Skirt accepts cutters up to 5/8" dia. Has 1/4-28 male threaded shaft for use with AT418 cutters. Can be assembled and disassembled without special tools. Split shaft and taper

locks pilot in place when cutter is tightened. Order cutters and pilots P/N AT442-SLS separately.



MICRO-STOP COUNTERSINK CAGES AND NYLONFOOT PIECE

2 Models available-one with NEEDLE bearing and one with BRONZE bushings. .001" increment depth adjustment. Positive adjustment lock. 1/4" dia. shank. 9/32" shaft travel. 9/16" cutter capacity. For 1/4-28 threaded cutters. Comes with "NO-MAR" foot piece. Rated at 3,000 RPM. Made in USA. With Bronze Bushings

P/N 12-01412..... With Needle Bearings P/N 12-00940



BRAKE RIVET SET

Use these sets with your hand squeezer. Will set brake rivets eliminating the possibility of cracking your brake pads P/N 12-00550.....

AT 409 SERIES STRAIGHT SHANK COUNTERSINK WITH INTERCHANGEABLE **CUTTERS AND PILOTS**



Assembly, consists of AT418E (1/2") cutter, AT416 pilot and AT409-1, 1/4" straight-shank. Has a collet-type shaft to securely hold the replaceable pilot.

When ordering specify: Part number of cutter and pilot dia. Assembly Example: AT409 with 100° cutter A418E & 1/8 pilot. (AT416-57) Adapter only P/N AT409-1

AT418 STOP COUNTERSINK CUTTERS



Three-straight flute replaceable pilot cutters with female thread. These cutters are designed with extra deep flute to permit numerous resharpenings and radial clearance to assure fast smooth cutting.

For Replaceable Pilots Refer to AT416 Series. Used With AT418

Part No.	Cutter Dia.	Thread Size	Pilot Hole	Price
AT418A-4	1/4"	1/4 - 28	.086	
AT418D-4	7/16"	1/4 - 28	.086	
AT418E-4	1/2"	1/4 - 28	.086	

120° AT418 COUNTERSINK CUTTER

Same type cutter as described above except with 120° Cutter Angle. 7/16" Cutter Diameter. P/N AT418D-7

AT416 PILOTS

Fit AT418 cutters. Undercut permits head to seat on cutter angle. Order by Part No. in table below.

Order by part Number..... Ea.

Part No.	Head Dia. "D"	Part No.	Head Dia. "D"
AT416-2	#40	AT416-56	3/32
AT416-12	#30	AT416-57	1/8
AT416-21	#21	AT416-59	5/32
AT416-31	#11	AT416-61	3/16
AT416-32	#10	AT416-63	7/32
		AT416-65	1/4