

SUNEX TOOLS

SUNEX PNEUMATIC TOOLS

1/4" DRIVE MINI AIR RATCHET WRENCH



| SX1068 Specification | |
|--------------------------------|-----|
| Free Speed (RPM) @90PSI | 230 |
| Torque (ft. lbs.) @90PSI | 25 |
| Square Drive | 1/4 |
| Min. Hose Size | 2/8 |
| Recommended Air Pressure (PSI) | 90 |
| Average Air Consumption (CFM) | 3 |
| Sound Level (dBA) | 87 |
| Length (In.) | 8 |

- * Lever throttle for positive speed control
- * Ball detent socket retainer
- * Rear exhaust
- * Also available: 1/4" head kit

P/N 12-01932

1/2" DRIVE IMPACT WRENCH



| SX634CZ Specification | |
|--------------------------------|--------|
| Square Drive (In.) | 1/2 |
| Max. Torque (ft. lbs @90PSI) | 220 |
| Working Torque (ft. lbs.) | 50-190 |
| Free Speed (RPM@90PSI) | 7,000 |
| Air Inlet (NPT) | 1/4 |
| Recommended Air Pressure (PSI) | 90 |
| Average Air Consumption (CFM) | 4 |
| Sound Level (dBA) | 103 |
| Length (In.) | 7 |

- * Rocket dog clutch mechanism
- * Built-in regulator for positive speed control
- * Balanced design for ease of handling
- * Protective PVC rubber cover
- * The most economical 1/2" Impact wrench

P/N 12-01936

3/8" DRIVE PISTOL GRIP IMPACT WRENCH



| SX821A Specification | |
|--------------------------------|--------|
| Square Drive (In.) | 3/8 |
| Max. Torque (ft. lbs @90PSI) | 75 |
| Working Torque (ft. lbs.) | 30-60 |
| Free Speed (RPM@90PSI) | 10,000 |
| Air Inlet (NPT) | 1/4 |
| Recommended Air Pressure (PSI) | 90 |
| Average Air Consumption (CFM) | 4 |
| Sound Level (dBA) | 84 |
| Length (In.) | 5 |

- * Ring socket retainer for rapid socket changes
- * Front bumper for added protection
- * Built-in regulator for added protection
- * Reliable dog clutch mechanism for dependable service
- * Reliable dog clutch mechanism for dependable service

P/N 12-01937

1/2" DRIVE HEAVY DUTY IMPACT WRENCH



| SX821A Specification | |
|--------------------------------|--------|
| Square Drive (In.) | 1/2 |
| Max. Torque (ft. lbs @90PSI) | 450 |
| Working Torque (ft. lbs.) | 25-350 |
| Free Speed (RPM@90PSI) | 7,000 |
| Air Inlet (NPT) | 1/4 |
| Recommended Air Pressure (PSI) | 90 |
| Average Air Consumption (CFM) | 4 |
| Sound Level (dBA) | 103 |
| Length (In.) | 7.4 |

- * High-powered pin clutch delivers over 450 ft. lbs. of maximum torque
- * Working torque range 25-350 ft. lbs.
- * Rear knob regulator and variable speed trigger allow precise speed control
- * Cushion grip design for comfort and control

P/N 12-01938

MEDIUM DUTY AIR HAMMER



| SX275B Specification | |
|--------------------------------|--------|
| Blows Per Minute | 3,000 |
| Bore (In.) | 1 1/16 |
| Stroke (In.) | 2-5/8 |
| Air Inlet (NPT) | 1/4 |
| Min. Hose Size (I.D.) | 3/8 |
| Recommended Air Pressure (PSI) | 90 |
| Average Air Consumption (CFM) | 4 |
| Sound Level (dBA) | 105 |
| Length (In.) | 6.75 |

- * Built-in regulator
- * Accepts .401" Parker taper shank chisels
- * An excellent general purpose hammer
- * Quick change retainer spring

P/N 12-01935

SHORT AIR HAMMER



| SX821A Specification | |
|--------------------------------|-------|
| Blows Per Minute | 4,500 |
| Bore (In.) | 1-5/8 |
| Stroke (In.) | 1-5/8 |
| Air Inlet (NPT) | 1/4 |
| Min. Hose Size (I.D.) | 3/8 |
| Recommended Air Pressure (PSI) | 90 |
| Average Air Consumption (CFM) | 4 |
| Sound Level (dBA) | 105 |
| Length (In.) | 5.5 |

- * Built-in regulator
- * Accepts .401" Parker taper shank chisels
- * Ideal for standard duty applications
- * 3 pc. chisel set included
- * Quick change retainer spring

P/N 12-01934

SUNEX SANDING TOOLS

1/4" MINI DIE GRINDER



| SXC201 Specification | |
|-----------------------------|--------|
| Collect Size (In.) | 1/4 |
| Length (In.) | 6.1 |
| Maximum Speed (RPM) | 25,000 |
| Air Inlet (In.) | 1/4 |
| Minimum Hose Diameter (In.) | 3/8 |
| Avg. Air Consumption (CFM) | 2.1 |
| Weight (Lbs.) | 0.9 |

- * Durable comfort grip
- * Twin bearing spindle increases precision and decreases vibration
- * 360° adjustable rear exhaust directs air away from work
- * Built-in speed regulator
- * Locking throttle lever for safety

PN 12-01939

1/4" MEDIUM DIE GRINDER



| SXC205 Specification | |
|-----------------------------|--------|
| Collect Size (In.) | 1/4 |
| Length (In.) | 7 |
| Maximum Speed (RPM) | 22,000 |
| Air Inlet (In.) | 1/4 |
| Minimum Hose Diameter (In.) | 3/8 |
| Avg. Air Consumption (CFM) | 3 |
| Weight (Lbs.) | 1.3 |

- * Durable comfort grip
- * Twin bearing spindle increases precision and decreases vibration
- * 360° adjustable rear exhaust directs air away from work
- * Built-in speed regulator
- * Locking throttle lever for safety

PN 12-01940

3" UTILITY CUT-OFF TOOL



| SXC209 Specification | |
|-----------------------------|--------|
| Wheel Size (In.) | 3 |
| Length (In.) | 7.6 |
| Maximum Speed (RPM) | 21,000 |
| Air Inlet (In.) | 1/4 |
| Minimum Hose Diameter (In.) | 3/8 |
| Avg. Air Consumption (CFM) | 3 |
| Weight (Lbs.) | 1.8 |

- * Durable comfort grip
- * Twin bearing spindle
- * 360° adjustable rear exhaust directs air away from work
- * Built-in speed regulator
- * Locking throttle lever for safety
- * High-torque motor for maximum efficiency

PN 12-01941

2" ANGLE GRINDER



| SXC606 Specification | |
|-----------------------------|--------|
| Wheel Size (In.) | 2 |
| Length (In.) | 7.4 |
| Maximum Speed (RPM) | 15,000 |
| Air Inlet (In.) | 1/4 |
| Minimum Hose Diameter (In.) | 3/8 |
| Avg. Air Consumption (CFM) | 3 |
| Weight (Lbs.) | 1.6 |

- * Durable comfort grip
- * 90° angle head for restricted areas
- * 360° adjustable rear exhaust directs air away from work
- * Built-in speed regulator
- * Locking throttle lever for safety
- * High-torque motor for maximum efficiency

PN 12-01942

4.5" ANGLE GRINDER



| SXC610 Specification | |
|-----------------------------|--------|
| Wheel Size (In.) | 4.5 |
| Length (In.) | 9.6 |
| Maximum Speed (RPM) | 10,000 |
| Air Inlet (In.) | 1/4 |
| Minimum Hose Diameter (In.) | 3/8 |
| Avg. Air Consumption (CFM) | 5 |
| Weight (Lbs.) | 3.3 |

- * Durable comfort grip
- * 100° angle head for restricted areas
- * 360° adjustable rear exhaust directs air away from work
- * Built-in speed regulator
- * Locking throttle lever for safety
- * High-torque motor for maximum efficiency

PN 12-01943

TO