

SUNEX TOOLS

SUNEX 20 TON CAPACITY AIR BOTTLE JACK



Dimensions (In.)-6.5 x 8.9

* Designed for operating either manually or pneumatically * Air hose can swivel in any direction * Fitted with safety valve to prevent overloading * Two piece handle allows for easy pumping * Extension screw gives added height when necessary * Minimum air pressure required is 90 PSI, 7 Bars * Double spring return
4920BAH Specifications: Capacity (Tons)-20, Power Lift (In.) -7, Closed Height (In.) -10.5, Raised Height (In.) -20.1, Add. Screw Adj. (In.)-3.5, Base P/N 12-01958



SUNEX C-CLAMPS

*4" * Provides sure, non-slip clamping on all shapes * Drop-forged steel for greater strength and durability * Zinc-plated acme thread screw for accurate control
P/N 12-01944

4 PIECE 3/8 INCH DRIVE UNIVERSAL SPARK PLUG SOCKET SET



* All four sized spark plug sockets in one convenient set * Fully polished chrome vanadium alloy steel for durability * Universal joint design for easy access in confined areas * Rubber inserts hold spark plug securely during installation and removal * Includes new 9/16" size * Convenient blow mold case * Fully guaranteed
87602 Specifications: 8844-9/16, 8844-5/8, 8844-3/4, 8844-13/16
P/N 12-01966

8 PIECE PROFESSIONAL SCREWDRIVER SET - ORANGE



* Includes 5 flat tip drivers and 3 Phillips tip drivers * Hardened chrome vanadium shafts * Vapor blasted magnetic tips * Packaged in heavy molded plastic tray for storage * Hex bolsters on most sizes for extra turning power
87602 Specifications: 98061-3/8" x 8", 98062-5/16" x 6, 98063-1/4" x 4", 98064-3/16" x 3", 98065-1/4" x 1-1/2", 98066-#2 Phillips x 4", 98067-#1 Phillips x 3", 98068-#2 Phillips x 1-1/2" P/N 12-01974

SUNEX DELUXE CREEPER



5. Height (Headrest Up)-9.5, Shipping Weight (lbs.)-29.0, Bed Size-30.625 x 16.5 x 2.5

* 1" Rugged steel tube construction * Oversize frame for added comfort * Tapered frame and head rest for extra clearance in tight areas * 3-1/2" Heavy duty chrome finished casters with rubber tread * 5-Position stick shift headrest adjustment system * Rear drop frame design for extra leg comfort
8515 Specifications: Length (In.)-45.5, Width (In.)-19, Height (Headrest Down)-11.5, Shipping Weight (lbs.)-29.0, Bed Size-30.625 x 16.5 x 2.5
P/N 12-01964



SUNEX SERVICE CART WITH LOCKING TOP & DRAWER

* 8016 - 3 Drawer Unit * 8011 - Large Locking Screwdriver/Pry Bar holder * 8004 - Side Work Bench * 8014 - Leg extension Drawer liner sold separately Note: This item is purchased as a complete unit with the accessories listed above.
8013ADLX Specifications: Load capacity (lbs.)-350, Shipping weight (lbs.)-115.5, Color: Blue-8013ABDLX, 8844-13/16-13/16"
P/N 12-01962

SUNEX SERVICE CART WITH LOCKING TOP & DRAWER



* This combination makes for the ultimate cart * The locking drawer and locking top are keyed the same, so the user only has one set of keys * Clip-on roller-bearing slides on drawer * Large, easy to maneuver 4" wheels: 2 locking and 2 standard, Chrome 16 gauge steel frame, Durable powder coated finish, 3" deep shelves, Available colors: red, blue, black & yellow
8013A Specifications: Load capacity (lbs.)-350, Shipping weight (lbs.)-69.5
P/N 12-01963



SUNEX 6 INCH VISE

* 2 locking mechanism for stability * Made from cast iron with steel handle threads
87602 Specifications: Base Swivel- 360 deg.
P/N 12-01961



SUNEX 3/8 INCH CUTTING WHEEL - 5 PCS.

* For general purpose metal cutting 3" x 1-1/16" double reinforced * Use with 3/8" arbor * Do not exceed 20,000 RPMs * Comply with ANSI B7.1/OSHA regulations
87602 Specifications: Diameter (In.)-3, Qty. Included -5, Max RPM -25,000
P/N 12-01965

6 INCH BENCH GRINDER WITH LIGHT



* Bright, flexible work light * Has two 6" grit wheels: coarse 36 and medium 60 * Each wheel has protective spark guard and adjustable eye shield * Mounting holes and rubber feet make grinder easy to mount on a stand (optional - part #5003 or 5005) or use on an approved worktable or workbench * Conveniently placed, easy to use on/off switch * Long, 6-foot power cord * Cast iron base for durability * Ball bearing construction for smooth operation * 1/2" Arbor accepts standard 6" wheel * UL & CSA Listed * Includes: eye shields (RS500119B) & tool rests (RS500135B)
5001A Specifications: Power-1/2 HP Motor, No Load speed .3450 RPM Motor -3.5 Amp, Voltage -115V/60Hz, Shipping Wt. (Lbs) -22
P/N 12-01959



5 TON CAPACITY 8-WAY, 2-3 JAW REVERSIBLE PULLER

* Can be assembled to make a two or three jaw puller when additional stability is needed * Reversible jaw design for added versatility and a broader range of pulling capability * Ideal for pulling gears, bearings, pulleys and other press fit parts
3908 Specifications: Maximum reach (in.)-5.5, Maximum spread (in.) -7
P/N 12-01957



3/16 INCH HEAVY DUTY RIVET GUN

* Sets all conventional, standard blind rivets and all structural blind rivets, mono bolts and t-rivets up to and including 3/16" diameter in all materials * Comes with nose pieces in 3/32", 1/8", 5/32", and 3/16" sizes * Features a pulling (traction) power of 1,983 lbf @90PSI * Forged aluminum handle * Nose pieces stored conveniently underneath base of gun * Minimum air pressure required is 90 PSI, 7 Bars * Includes blow molded storage case
SX0918T Specifications: Air Pressure (PSI) -75-90, Stroke Length (In.) -11/16, Height (In.) -12-3/8, Weight (Lbs.) -3.70, Min. Hose Size (I.D.) -3/8, Air Inlet Size (NPT) -1/4
P/N 12-01933

TO