

FIRE EXTINGUISHERS – RESCUE EQUIPMENT



H3R AVIATION FIRE EXTINGUISHERS

The FAA recommends and/or requires Halon fire extinguishers on aircraft. H3Rs Halon fire extinguishers are the extinguishers of choice in the aviation industry. They cause no mess or damage, and do not require taking a plane out of service for clean-up; a costly process for both the aircraft owner and insurance carrier. The heat-seeking quality of the Halon gas makes it a superior fire fighting agent.

DISPOSABLE, LOW-MAINTENANCE HALON 1211-1301 BLEND -

Contain a proprietary blend of the "liquid streaming agent," Halon 1211, and the gaseous "total flooding agent," Halon 1301. The blend's power lies in the Halon 1301, which is both a firefighting agent and a propellant. Low maintenance and non-rechargeable. Lightweight aluminum canister Disposable. Tested to ANSI/UL 711 and UL 1093. Meets DOT requirements Meets the requirements in Advisory Circular 20-42C, "Hand Held Extinguishers for Aircraft" and/or NFPA 408, "Standard for Aircraft Hand Portable Fire Extinguishers" 12-year shelf life

RECHARGEABLE, STURDY INDUSTRY-STANDARD HALON 1211 -

Required on commercial transport aircraft. Although classified a "liquid streaming agent," Halon 1211 also performs remarkably well as a "total flooding agent," seeking out and extinguishing fires in inaccessible places. A 6-year maintenance and 12-year hydrostatic test are required. Rugged steel cylinder. Pressure gauge enables easy confirmation of charge. Tested to ANSI/UL 711 and UL 1093. Meets DOT requirements. Meets the requirements in Advisory Circular 20-42C, "Hand Held Extinguishers for Aircraft" and/or NFPA 408, "Standard for Aircraft Hand Portable Fire Extinguishers"

HALON 1211-1301 BLEND UNITS	Part No.	Range	Price
RT A400 - 14 oz. (UL Rating 2B:C)	13-07650	4-6 ft	-
RT A600 - 1.2 lb. (UL Rating 2B:C)	13-07655	6-8 ft	-
RT A1200 - 2.5 lb. (UL Rating 5B:C)	13-07660	7-9 ft	-

HALON 1211 UNITS	Part No.	Range	Price
A344T - 1.3 lb. (UL Rating 2B:C)	13-01993	9-12 ft	-
A344TC - 1.3 lb. (UL Rating 2B:C)	13-02546	9-12 ft	-
C352TS - 2.5 lb. (UL Rating 5B:C)	13-01966	9-15 ft	-
C352TSL - 2.5 lb. (UL Rating 5B:C)	13-02547	9-15 ft	-
C354TS - 3.0 lb. (UL Rating 5B:C)	13-02548	9-15 ft	-
A1600 - 3.5 lb. (UL Rating 1A:5B:C)	13-07665	8-10 ft	-
B355T - 5.0 lb. (UL Rating 10B:C)	13-02545	9-15 ft	-
B369 - 15.7 lb. (UL rating 1A:10B:C)	13-02557	12-18 ft	-
B371 - 19.9 lb. (UL rating 2A:40B:C)	13-02558	12-18 ft	-

FIRE EXTINGUISHER BRACKETS

- BKT400** - Brackett for the RT-A400 Fire Extinguisher
P/N 13-06166.....
- BKT600** - Brackett for the RT-A600 Fire Extinguisher
P/N 13-06167.....
- BKT1200** - Brackett for the RT-A1200 fire Extinguisher
P/N 13-06168.....
- 845** - Brackett for the A344T Fire Extinguisher
P/N 13-06170.....
- 845** - Brackett for the A344TC Fire Extinguisher
P/N 13-06171.....
- 817S** - Brackett for the C352TS, C352TSC, C354TS Fire Extinguisher
P/N 13-06172.....
- BKT1600** - Brackett for the A1600 Fire Extinguisher
P/N 13-06169.....



H3R BILLET MOUNTS

H3R Performance hand held 1 lb. and 2.5 lb. fire extinguishers come standard with aviation style mounting brackets. Stylish and versatile billet mounting accessories are also available. Band clamps fit 2.6" or 3.0" diameter fire extinguishers, and can be combined with the flat surface mount or either of the two roll bar mounts. Available in polished and brushed finishes. One year limited warranty.

- Polished - Band clamp for 1.0/1.4 lb. fire extinguishers
P/N13-06062.....
- Brushed - Band clamp for 1.0/1.4 lb. fire extinguishers
P/N 13-06065.....
- Polished - Band clamp for 2.5 lb. fire extinguishers
P/N 13-06066.....
- Brushed - Band clamp for 2.5 lb. fire extinguishers
P/N 13-06067.....
- Polished -Flat surface mount P/N 13-06068.....
- Brushed -Flat surface mount P/N 13-06069.....

RECHARGEABLE, DURABLE EPA-APPROVED HALOTRON 1™

While it is less powerful pound for pound than Halon 1211, Halotron 1 offers all of Halon 1211's clean agent benefits, and Halotron 1 is less damaging to the ozone layer. H3R Aviation offers two Halotron 1 fire extinguishers: one FAA-approved unit for aircraft use and one wheeled unit for the flight line/ramp. These rechargeable extinguishers have pressure gauges and require a 6-year maintenance and a 12-year hydrostatic test. P/N 13-02562



FIREFLY PLUS FLASHLIGHT/STROBE



The Firefly Plus is a flashlight/emergency locator strobe which is visible for over one mile. The operating life of the strobe is 10 hours, and 2 hours for the flashlight (continuous). Firefly Plus operates on 2 AA batteries (not included) and made of durable ABS plastic. Waterproof & weighs 4 oz. Size: 2" dia. x 5-3/8"h. Excellent addition to any aircraft or home emergency kit. P/N 13-54050

C-STROBE LIGHT

The C-Strobe Light is a life preserver signaling emergency strobe which attaches to a life jacket or life vest with a steel pin or Velcro straps. The omni-directional strobe light is visible up to 2 miles. C-Strobe features a slim, lightweight, waterproof case and operates more than 8 hrs (continuous). Operates on 2 AA alkaline batteries (not included). P/N 13-54020



C LIGHT

The C Light is a life preserver signaling emergency light which attaches easily to a life vest or jacket with a stainless steel pin or Velcro strap. The intense incandescent light is visible for up to 2 miles depending on conditions. The lens intensifies light 20 times brighter than comparable products. Operates on 2 AA alkaline batteries (not included). Operates more than 8 hours (continuous). P/N13-54030



RAPIDFIRE VEST LIGHT

RapidFire Vest Light is a self-contained emergency rescue lamp. It's small, compact, rugged, and waterproof and attaches to a standard life vest. It automatically lights when vest is inflated or on manual pull-pin activation. Provides 8 hours continuous light output once activated. Single use light. P/N 13-54040



MINI B 300 PERSONAL RESCUE TRANSMITTER

- In-line speaker emits audio warble to confirm activation and transmission of distress signal or to notify of accidental activation
- Exclusive ACR audio indication of transmission allows effective self-test
- User-replaceable battery; unit uses inexpensive, easy-to-obtain common lithium camera battery, Duracell DL223A (or equivalent)
- Frequency stability exceeds ETS 300 152 standard; meets rules for satellite detection
- Perfect for use as Crew-Overboard system when combined with Vecta2™ Direction Finder
- Floats if dropped overboard • 121.5 MHz (SAR frequency) provides rescue forces with pinpoint homing
- Antenna maximizes peak effective radiating power when fully extended. Compact size with antenna folded; durable double-braided antenna resists distortion when packed for extended periods
- LED indicator confirms transmission
- Battery installation instructions included

Operating life: 24 hours @ -20°C (-4°F) P/N 13-02416



RESCUE LASER FLARE MAGNUM™

Ahand-held nighttime laser signaling device that provides a convenient, effective way to signal a rescue party up to 20 miles (32 km) away, depending on atmospheric conditions. It's ease of operation, long life and waterproof design makes it the perfect survival signaling device. Unlike conventional pyrotechnic flares, the Rescue Laser Flare™ is non-flammable, non-hazardous and can operate continuously for 72 hours on two replaceable AA batteries. 72 Hour P/N 13-01924..... 15 Hour P/N 13-01923.....



ACTIVE EXTINGUISHING LINE

Active Extinguishing Line is totally independent, 1kg, fire extinguishing system from any power source. Its main secret lies in the heat detector in a form of a line made out of special laser predriller polymer, which will react instantly to any source of heat or fire. This line (heat detector) is connected to reservoir containing fire-extinguishing agent: hexafluoropropane FE-36. Inside of the protected device (equipment) a loop made out of the heat detector breaks, creating a mini sprinkler, directly over source of fire or heat, extinguishing it instantly. In a moment of activation the system closed circuit switch collapses sending a signal informing of fire. For experimental aircraft only. Ask for status of pending STCs.....P/N 13-03266

