ICK BOND FASTENER

CLICK BOND FASTENERS

Click Bond Fasteners mount to surfaces with adhesive. They are assembled in a disposable, self-fixturing device of plastic that aligns and holds the fastener in position and under controlled pressure while the bonding material cures. After the installation is completed, the holding fixture is removed and the conventional attachment is made to the fastener. Bonded fasteners eliminate welding or drilling surfaces and result in reinforced substrate strength, leakproof and corrosion resistant attachments. Aircraft Spruce & Specialty Co. offers Click Bond Fasteners in convenient, pre-packaged kits as shown

CABLE TIE MOUNT KIT



Each cable tie mount in this kit is pre-assembled in a temporary, easy-to-remove fixture that holds the cable tie mount in place and under pressure while the adhesive cures. No additional installation tools are needed. The kit includes four CB3019AA3N cable tie mounts with nylon ties (5" 40 lbs.), one adhesive packet, surface prepara-P/N 04-06000

tion materials, and installations. HA

FLOATING NUTPLATE KIT



The Click Bond adhesive bonded floating nutplate has a metal base and is installed using a disposable, elastomeric fixture that temporarily holds the nutplate in place and under pressure while the adhesive cures. The fixture prevents fouling of the clearance hole. No additional tools are needed for making the nutplate attachment. This fastener meets or exceeds the standards

set by MIL-N-25027 for push-out, torque-out, and cycle life. Bonded nutplates eliminate composite damaging rivets, reinforce the structure, and reduce installation time. The kit includes four CB2009A3S floating nutplates (10-32) with aluminum baseplate, one adhesive packet, surface preparation materials, and instructions.

REPAIR PATCH KIT



These self-fixturing surface mounted patches repair small holes and fastener leaks without access to the reverse side of the surface. The patches are adhesively bonded to flat or curved surfaces with the aid of an integral, disposable fixture. The high peel strength adhesive allows the patches to withstand supersonic flight, cleaning, de-icing,

and paint stripping. Patches can be removed easily with heat application. The kit includes one CP125-000-005A1A1 aluminum repair patch (.005 thick and 1.25 inch diameter), one adhesive packet, surface preparation materials, and instructions.

P/N 04-06015




CB 200 ACRYLIC ADHESIVE

A high strength, two part adhesive. 3.5 gram package. One package is usually sufficient to do five of any Click Bond fasteners P/N 04-06040

STUD KITS

CLICK BOND



ers (1/4-20), one adhesive packet, surface preparation materials, and instructions. The Fiberglass Base Stud Kit includes two CS125-1032-12G-CR fiberglass large base stainless studs, two stainless nylocks/ washers (10-32), one adhesive packet, surface preparation materials, and instructions.

Metal Small Base Stud Kit	. P/N 04-06020
Metal Large Base Stud Kit	. P/N 04-06025
Fiberglass Base Stud Kit	. P/N 04-06030

EZ-POINT NUTS & STUDS FOR COMPOSITES



Creating a hard point in a composite laminated structure has never been easier. Simply drill a hole, prep the area, apply structural adhesive to the alodined, cleaned surface of the EZ-Point and snap into place. Simple and clean. For secondary structural applications, apply three plies of bid cloth to the area. Un-glassed samples were tested to failure in excess of 200 lbs. in shear. Glassed samples exceeded testing ability at over 500 lbs. Perfect for Adel clamps, trim and auto pilot servos, hydrau-

Available in 8-32, 10-32, 1/4 - 20, lics, anything but primary structure. 1/4 - 28, your choice of locking, blind and studs. Used extensively in the installation of the Flesher 360 interior for the Lancair.

STUDS			BLIND NUTS			LOCKING NUTS			
THREAD	P/N	\$ EA	THREAD	P/N	\$ EA	THREAD	P/N	\$ EA	
8-32	04-06330		8-32	04-06350		8-32	04-06370		
10-32	04-06335		10-32	04-06355		10-32	04-06375		
1/4 - 20	04-06340		1/4 - 20	04-06360		1/4 - 28	04-06380		
						1/4 - 28	04-06385		

EZ-POINT STRIPS FOR COMPOSITES



Take the guesswork out of nut plate spacing with EZ-Point Strips. They maintain consistent spacing while remaining flexible enough to conform to curvature. Perfect for cowling attachments, Access doors, removable wingtips, anywhere you would use a standard 10/32 or 8/32 nut plate. Locking threads, available in one, two and three inch centers.

0	old in one-loot sections.			
	8-32 thread, 1" centers	P/N	04-06450	 ea.
	8-32 thread, 2" centers	P/N	04-06455	 ea.
	8-32 thread, 3" centers	P/N	04-06460	 ea.
	10-32 thread, 1" centers	P/N	04-06465	 ea.
	10-32 thread, 3" centers	P/N	04-06475	 ea.