

CLAMPS



MS21919 DG & WDG CLAMPS

Loop-type cushioned aluminum alloy clamp. Cushion (non-fuel resistant) is bonded to inner surface and edges of clamp. WDG clamps are cushion wedge type. Cushion assures tight fit and eliminates vibration, thus preventing line abrasion.

Tube Dia.	Dash No.	Price Each	Dash No.	Price Each	Tube Dia.	Dash No.	Price Each	Dash No.	Price Each
1/8	DG2	.	WDG2	.	1-5/16	DG21	.	WDG21	.
3/16	DG3	.	WDG3	.	1-3/8	DG22	.	WDG22	.
1/4	DG4	.	WDG4	.	1-7/16	DG23	.	WDG23	.
5/16	DG5	.	WDG5	.	1-1/2	DG24	.	WDG24	.
3/8	DG6	.	WDG6	.	1-9/16	DG25	.	WDG25	.
7/16	DG7	.	WDG7	.	1-5/8	DG26	.	WDG26	.
1/2	DG8	.	WDG8	.	1-3/4	DG28	.	WDG28	.
9/16	DG9	.	WDG9	.	1-7/8	DG30	.		
5/8	DG10	.	WDG10	.	1-15/16	DG31	.		
11/16	DG11	.	WDG11	.	2	DG32	.		
3/4	DG12	.	WDG12	.	2-1/16	DG33	.		
13/16	DG13	.	WDG13	.	2-1/8	DG34	.		
7/8	DG14	.	WDG14	.	2-1/4	DG36	.		
15/16	DG15	.	WDG15	.	2-3/8	DG38	.		
1	DG16	.	WDG16	.	2-1/2	DG40	.		
1-1/16	DG17	.	WDG17	.	2-5/8	DG42	.		
1-1/8	DG18	.	WDG18	.	2-3/4	DG44	.		
1-3/16	DG19	.	WDG19	.	2-7/8	DG46	.		
1-1/4	DG20	.	WDG20	.	3	DG48	.		
					3-1/8	DG50	.		

Less 15% in lots of 50. May be assorted.

AP



QS 100 HOSE CLAMPS

Tangential worm-screw type for use on fuel, oil, air and coolant lines. Worm drive provides uniform clamping pressure without distorting hose. The QS100 series has stainless steel band with cadmium-plated carbon steel thumb screw. To attach, just push housing to the desired position on the band, snugly around hose, & the threads of the worm screw will drop into the slots. Tighten thumb screw with finger pressure - no tools required.

QS100 Dash No.	Dia. Range (In.)		Price Each	QS100 Dash No.	Dia. Range (In.)		Price Each
	Min.	Max.			Min.	Max.	
M6W	7/16	25/32	.	M24W	1-1/16	2	.
M8W	1/2	29/32	.	M28W	1-1/16	2-1/4	.
M10W	9/16	1-1/16	.	M32W	1-9/16	2-1/2	.
M12W	11/16	1-1/4	.	M36W	1-13/16	2-3/4	.
M16W	13/16	1-1/2	.	M40W	2-1/16	3	.

Less 15% in lots of 50. May be assorted.



QS 200 HOSE CLAMPS

Aero-Seal stainless steel clamps are for industrial & aircraft applications. This tangential worm-screw type clamp is for use on fuel, oil, air & coolant lines. The worm drive provides uniform clamping pressure without distorting hose. Attach by pushing housing snugly around the hose to desired position on the band—the threads of the worm screw will drop into slots. Tighten slotted head with screwdriver.

QS200 Dash No.	Dia. Range (In.)		Price Each	QS200 Dash No.	Dia. Range (In.)		Price Each
	Min.	Max.			Min.	Max.	
-06H	7/16	25/32	.	-44H	2-5/16	3-1/4	.
-08H	1/2	29/32	.	-48H	2-9/16	3-1/2	.
-10H	9/16	1-1/16	.	-52H	2-13/16	3-3/4	.
-12H	11/16	1-1/4	.	-56H	3-1/16	4	.
-16H	13/16	1-1/2	.	-60H	3-5/16	4-1/4	.
-20H	13/16	1-3/4	.	-64H	3-9/16	4-1/2	.
-24H	1-1/16	2	.	-72H	4-1/8	5	.
-28H	1-5/16	2-1/4	.	-80H	4-5/8	5-1/2	.
-32H	1-9/16	2-1/2	.	-88H	5-1/8	6	.
-36H	1-13/16	2-3/4	.	-96H	5-5/8	6-1/2	.
-40H	2-1/16	3	.	---	---	---	---

Less 15% in lots of 50. May be assorted.

BREEZE AERO-SEAL STAINLESS CLAMP KITS

Pack A : Contains 2 each QS200 -52H, -64H, -72H and -80H.

P/N 05-00942.....

Pack B : Contains 2 each QS200 -8H, -12H, -24H, -32H, -40H, & -64H.

P/N 05-01340.....



SNAPPER CLAMPS

A quick ratchet closure provides specific take-up, eliminating excessive tightening which may mutilate the hose.

3/8" for 1/4" fuel line

P/N 05-00940.....

1", for radiator hose

P/N 05-00941.....



AN742 PLAIN CLAMPS

Plain loop-type line support clamps, made of aluminum alloy meeting specification QQ-A-362, condition T. Heat-treated to a minimum tensile strength of 50,000 PSI.

Dash No.	For Tube O. D. (In.)	Price Each	Dash No.	For Tube O. D. (In.)	Price Each
-D3	3/16	.	-D8	1/2	.
-D4	1/4	.	-D10	5/8	.
-D5	5/16	.	-D12	3/4	.
-D6	3/8	.	-D15	15/16	.
-D7	7/16	.	-D16	1	.

Less 15% in lots of 50. May be assorted.



BREEZE MINIATURE CLAMPS

The best clamp for small diameter hose and tubing. Stainless steel band and housing with plated carbon steel screw. Applies an even circumferential pressure with less torque.

7/32" to 5/8"P/N 6504 Ea.

7/16" to 7/8"P/N 6506 Ea.

OETIKER STEPLESS SCREW CLAMPS



Oetiker Stepless Screw Clamps feature a unique tongue-in-groove design to provide a perfect 360° seal. Their narrow band width of 9 mm is designed to fit grooved objects. They are ideal where specialty clamping needs have to be met and the application calls for a smooth inner surface such as on flexible duct sleeves.

The tongue-in-groove design provides that "stepless" complete seal. Manufactured using 300 AISI series stainless steel.

P/N	Clamping O.D. Range Inches	Price Each	P/N	Clamping O.D. Range Inches	Price Each
028-9	13/16" - 1-1/8"	.	090-9	3-5/16" - 3-1/2"	.
031-9	15/16" - 1-1/4"	.	095-9	3-1/2" - 3-3/4"	.
032-9	1-1/16" - 1-1/4"	.	100-9	3-11/16" - 3-15/16"	.
036-9	1-1/4" - 1-7/16"	.	105-9	3-15/16" - 4-1/8"	.
040-9	1-3/8" - 1-9/16"	.	110-9	4-1/8" - 4-5/16"	.
045-9	1-9/16" - 1-3/4"	.	115-9	4-5/16" - 4-1/2"	.
050-9	1-3/4" - 2"	.	120-9	4-1/2" - 4-11/16"	.
055-9	1-15/16" - 2-1/8"	.	125-9	4-11/16" - 4-15/16"	.
060-9	2-1/8" - 2-3/8"	.	130-9	4-7/8" - 5-1/8"	.
065-9	2-5/16" - 2-9/16"	.	135-9	5-1/16" - 5-5/16"	.
070-9	2-9/16" - 2-3/4"	.	140-9	5-1/2" - 5-11/16"	.
075-9	2-3/4" - 3"	.	145-9	5-11/16" - 5-7/8"	.
080-9	2-15/16" - 3-1/8"	.	150-9	5-7/8" - 6-1/16"	.
085-9	3-1/8" - 3-5/16"	.	160-9	6-1/16" - 6-1/4"	.
			165-9	6-1/4" - 6-1/2"	.



LINE CLAMPS

These line clamps are lightweight but tough enough for the most rugged applications. Feature single piece .030" thick aluminum construction. No more messy bundles. Each clamp is shaped to hold braided line, tubing, or wiring securely, without pinching. Secured w/ standard tie wraps, these clamps keep movement and wear to a minimum. Can be adjusted to mount on any tubing from 3/4".

Size	P/N	Price	Size	P/N	Price
1/4"	05-00004	.	5/8"	05-00007	.
3/8"	05-00005	.	3/4"	05-00008	.
1/2"	05-00006	.	1"	05-00009	.

30 piece assortment - includes 5 of each clamp
P/N 05-02205.....