

MICROFLIGHT GAUGES

MICRO-1000 ENGINE GAUGES

Senders and probes are not included unless specifically noted. See over half of the page for senders, probes, and other accessories. 2" gauges are round. 2 1/4" gauges are square.



OIL PRESSURE ELECTRIC

MICRO-1000 oil pressure electric includes 1/8 NPT SDR.
 2 1/4" OP031..... P/N 10-01574
 2" OP030..... P/N 10-01572



OIL TEMPERATURE ELECTRIC

Includes 1/8 NPT Sender
 2 1/4" OT031..... P/N 10-01588
 2" OT030..... P/N 10-01586



HOUR METER

AC or DC Powered
 2 1/4" HO031..... P/N 10-01507
 2" HO030..... P/N 10-01506



DC VOLTMETER

2 1/4" VM031..... P/N 10-01641
 2" VM030..... P/N 10-01639



WATER TEMPERATURE

Includes 1/8 NPT Sender. All electrical gauges have air core movements.
 2 1/4" WT031..... P/N 10-01652
 2" WT030..... P/N 10-01650



AMMETER ±30 AMPS

2 1/4" AG031..... P/N 10-01319
 2" AG030..... P/N 10-01317

MICROFLIGHT SENDERS & ACCESSORIES



100# PRESSURE SENDER

HAS A 1/8" NPTF fitting.
 OP030.2..... P/N 10-01573.....



TUBING KIT

Nylon tubing with brass fittings.
 OP032.1..... P/N 10-01575.....
 OP032.2..... P/N 10-01576.....



KEY WEST REGULATOR

Advanced regulator/rectifier circuit provides steady 13.8 volt output regardless of load. Maximum output 220 watts, 16 amps. 10v signal pulse output for digital or MaxPac® tachs. Accepts AC input from 15 to 100 volts. Can be used with AC strobe. **Features:** * Extremely clean filtered DC output * Electronics designed to deliver 16 amps producing 220 watts * Efficiency: No "consumer" or "dummy" load required for proper operation * A beautiful and rugged lightweight package weighs just 16 ounces and is 3.5 x 2.5 x 1 inch * Protection from the environment: complete epoxy encapsulation to insure all-season operation * Ease of installation: crimp type ring terminals and wiring schematics provided with every unit P/N 11-03168.....



TEMPERATURE SENDERS

Single-station senders for water and oil temperature gauges.
 WT030.2..... P/N 10-01384.....
 OT030.2..... P/N 10-01587.....



SENDER ADAPTERS

Electric sender adapter. 3/8" NPT
 ADP04..... P/N 10-01311.....



METRIC ADAPTER

ADP06..... P/N 10-01313.....
 ADP07..... P/N 10-01314.....
 ADP08..... P/N 10-01315.....



FLOAT-TYPE FUEL PROBES

6-23" Probe. Adjustable, 6-23"; 240-33 ohms standard: 5-hole ASME pattern. Requires mounting kit. FGP031..... P/N 10-01489.....



UNIVERSAL PROBE MOUNT

Works well with plastic and other tank. Includes threaded attachment ring, gasket, and hardware. Standard 5-hole SAE pattern. FMK01..... P/N 10-01501.....



COLOR TINT LAMPS

Color tint lamp boots. Set of Boots. Changes your instrument backlighting to red for night flying. LB001..... P/N 10-01556.....

APPLICATION NOTE: Most current production Rotax® engines require 1/8NPT temperature and pressure senders.

IN