AIRCRAFT DESIGNER APPROVED TOOLS

The tools offered in this section have been selected by professional aircraft designers and builders as being either necessary or highly desirable for working with composite structures.


KUT-MASTER FOAM CUTTING FRAME



These custom-built foam cutting frames can help produce professional results in foam cutting for the amateur builder. Constructed of 1-1/8" O.D. aluminum tubing, the heli-arc welded frame is lightweight yet extremely durable. The frames come completely pre-wired and ready to attach to the voltage controls shown below, and a tensioning system maintains uniform wire tension throughout the cutting process. The frames are stocked in 3 standard lengths, and custom frames are available on request (send sketch). Cutting depth is 11". Weight- 5 lbs.

2 Ft. FrameP/N 01-15200
3 Ft FrameP/N 01-15300
4 Ft FrameP/N 01-15400

HOMEBUILDERS SPECIAL HOTWIRE KIT



An excellent new hot wire system consisting of a controller and transformer. Recommended by Rutan Aircraft Factory as a good system at a very



economical price P/N 01-15600

SAFETY WIRE



Type 302 stainless steel safety wire, for hot wire cutter. This is superior to nichrome wire, which is brittle and breaks easily. Specify .032" or .041" diameter wire.

.032" Dia. Wire, 25 Ft. Coil	. P/N 01-15725
.041" Dia. Wire, 25 Ft. Coil	. P/N 01-15825
1 Lb. Spool	. P/N 05-02687



INCONEL 600 HOT WIRE

Does	not	stretch.	Excellent	for	hotwiring	polyst	ty-
ene f	oam						
					5805	. '	ft.
0442		14/:00			F040		£1.



.041" Dia. Wire P/N 01-15810...... ft.

MUSIC WIRE

Music wire is high carbon steel and although very high in tensile strength, must be capable of wrapping around itself without showing signs of cracking. 156 ft. of .049" dia. wire per lb., 46 ft. of .090" dia. wire, per lb. 22 Gal. .049" Dia. (1 lbs.)..... P/N 03-49500090" Dia.(32Ga.,1lbs.) P/N 03-49600

TYPE 302 STAINLESS SPRING WIRE

062" Dia...... P/N 03-49610...... ft



MICHAEL **ENGINEERING EPOXY RATIO PUMPS**

This highly recommended pump, aptly called "Sticky-Stuff Dispenser", will save about \$50 in epoxy in building a VE type aircraft, plus time, mess, dermatitis, temper and risk of bad batches. Used by individual craftsmen and professionals alike, it is a practical engineering tool especially designed to eliminate the sticky, messy, costly hand proportioning of epoxy resins. It is well built and should last through the construction of dozens of aircraft. The Sticky-Stuff Dispenser assures accurate

measurement of low-viscosity (under 3,500 centipoises) unfilled epoxy resin. The standard Model A dispenser pump delivers a ratio of 100 parts of resin to 44 parts of hardener.

Adjustable Ratio Pump	P/N 01-16010
Rebuild Kit for 45:100 pump	P/N 01-00504
Small replacement container (qt).	P/N 01-15920
Large replacement container (gal)	P/N 01-15910
Stainless Steel Check Valve (Use	with Jeffco epoxies)

P/N 01-00258

CALRAD VARIABLE VOLTAGE CONTROL



A fine quality control to supply the electrical current for hot-wire cutting of styrofoam & PVC foam. One unit can serve to build many aircraft. Input 115VAC Output variable from 0-130VAC at 5amps Caution - fuse should be inserted in the secondary to protect the control in the event of a short circuit.

Size: 6"h, 5"w, 6"d

Input Cable: 6ft. heavy duty 3-prong Output Jack: 3 -prong AC jack Fuse Protected: 5A, 3AG: On/Off Rocker Type Power Switch AC Voltmeter: 0-150 VAC.

P/N 01-15500.....

COMPOSITE TOOL KIT

This kit includes an assortment of many of the commonly required					
This kit includes an assortment of many of the commonly required tools used in composite construction.					
QTY.	PART NO.	DESCRIPTION			
1	20W	Glass Shears			
1 box	01-25800	500 Mixing Sticks			
2 boxes	01-25700	12 oz. Mixing Cups			
2 boxes	01-25710	16 oz. Mixing Cups			
10	01-24899				
10	09-21200	1" Disposable Brushes			
10	09-21300	2" Disposable Brushes			
1		Electronic Scale			
2 boxes	01-36550	Latex Gloves			
1	GLR123D	1/2" x 3" Laminating Roller			
1	GLR12C	1/2" Corner Roller			
1	GLR26 2"	x 6" Plastic Grooved Roller			
Kit - P/N 01-00166					