


FILLISTER HEAD SCREWS - DRIVE SCREWS



AN500, AN501 DRILLED FILLISTER HEADSCREWS

AN500 (coarse thread) & AN501 (fine thread) slotted fillister head screws are fabricated from carbon steel. Tensile strength 60,000 PSI. Cadmium plated, Type II Class 3.
 * "A" IN DASH NO. DENOTES DRILLED HEAD

AN500 (Coarse Thread)				
AN500 Dash No.*	MS35265 Dash No.	Length (In.)	Thread Size	Price Each
-A4-3	MS35265-12	3/16	4-40	.
-A4-4	MS35265-13	1/4	4-40	.
-A4-5	MS35265-14	5/16	4-40	.
-A4-6	MS35265-15	1/4	4-40	.
-A4-7	MS35265-16	5/16	4-40	.
-A4-8	MS35265-17	1/4	4-40	.
-A4-10	MS35265-18	5/16	4-40	.
-A4-12	MS35265-19	1/4	4-40	.
-A6-4	MS35265-26	1/4	6-32	.
-A6-5	MS35265-27	5/16	6-32	.
-A6-6	MS35265-28	3/8	6-32	.
-A6-7	MS35265-29	7/16	6-32	.
-A6-8	MS35265-30	1/2	6-32	.
-A6-10	MS35265-31	5/8	6-32	.
-A6-12	MS35265-32	3/4	6-32	.
-A6-14	MS35265-33	7/8	6-32	.
-A8-4	MS35265-41	1/4	8-32	.
-A8-5	MS35265-42	5/16	8-32	.
-A8-6	MS35265-43	3/8	8-32	.
-A8-7	MS35265-44	7/16	8-32	.
-A8-8	MS35265-45	1/2	8-32	.
-A8-10	MS35265-46	5/8	8-32	.
-A8-12	MS35265-47	3/4	8-32	.
-A8-14	MS35265-48	7/8	8-32	.
-A8-16	MS35265-49	1	8-32	.
-A10-4	MS35265-59	1/4	10-24	.
-A10-5	MS35265-60	5/16	10-24	.
-A10-6	MS35265-61	3/8	10-24	.
-A10-7	MS35265-62	7/16	10-24	.
-A10-8	MS35265-63	1/2	10-24	.
-A10-10	MS35265-64	5/8	10-24	.
-A10-12	MS35265-65	3/4	10-24	.
-A10-16	MS35265-66	1	10-24	.
-A416-8	MS35265-79	1/2	1/4-20	.
-A416-10	MS35265-80	5/8	1/4-20	.
-416-12	MS35265-81	3/4	1/4-20	.
AN501 (Fine Thread)				
AN501 Dash No.*	MS35266 Dash No.	Length (In.)	Thread Size	Price Each
-8-12	-47	3/4	8-36	---
-A10-4	-59	1/4	10-32	.
-A10-6	-61	3/8	10-32	.
-A10-8	-63	1/2	10-32	.
-A10-10	-64	5/8	10-32	.
-A10-12	-65	3/4	10-32	.
-A10-14	-66	7/8	10-32	.
-A10-16	-67	1	10-32	.
-A10-20	-68	1-1/4	10-32	.

AN500AD (Coarse Thread/Stainless Steel)				
AN500 Dash No.*	MS35275 Dash No.	Length (In.)	Thread Size	Price Each
-AD2-2	-201	1/8	2/56	.
-AD2-3	-202	3/16	2/56	.
-AD2-4	-203	1/4	2/56	.
-AD2-5	-204	5/16	2/56	.
-AD2-6	-205	3/8	2/56	.
-AD2-7	-206	7/16	2/56	.
-AD2-8	-207	1/2	2/56	.
-AD2-10	-208	5/8	2/56	.
-AD2-12	-209	3/4	2/56	.
-AD4-2	-211	1/8	4-40	.
-AD4-3	-212	3/16	4-40	.
-AD4-4	-213	1/4	4-40	.
-AD4-6	-215	3/8	4-40	.
-AD4-7	-216	7/16	4-40	.
-AD4-8	-217	1/2	4-40	.
-AD4-10	-218	5/8	4-40	.
-AD4-12	-219	3/4	4-40	.
-AD4-14	-220	7/8	4-40	.
-AD4-16	-221	1	4-40	.
-AD6-4	-226	1/4	6-32	.
-AD6-5	-227	5/16	6-32	.
-AD6-6	-228	3/8	6-32	.
-AD6-7	-229	7/16	6-32	.
-AD6-8	-230	1/2	6-32	.
-AD6-10	-231	5/8	6-32	.
-AD6-12	-232	3/4	6-32	.
-AD6-14	-233	7/8	6-32	.
-AD6-16	-234	1	6-32	.
-AD8-5	-242	5/16	8-32	.
-AD8-6	-243	3/8	8-32	.
-AD8-7	-244	7/16	8-32	.
-AD8-8	-245	1/2	8-32	.
-AD8-10	-246	5/8	8-32	.
-AD8-12	-247	3/4	8-32	.
-AD8-14	-248	7/8	8-32	.
-AD8-16	-249	1	8-32	.
AN501AD (Fine Thread/Stainless Steel)				
AN501 Dash No.*	MS35276 Dash No.	Length (In.)	Thread Size	Price Each
-AD10-5	-260	5/16	10-32	.
-AD10-6	-261	3/8	10-32	.
-AD10-7	-262	7/16	10-32	.
-AD10-8	-263	1/2	10-32	.
-AD10-10	-264	5/8	10-32	.
-AD10-12	-265	3/4	10-32	.
-AD10-14	-266	7/8	10-32	.
-AD10-16	-267	1	10-32	.

HA



AN502, AN503 FILLISTER HEAD SCREWS

AN502 (fine thread) and AN503 (coarse thread) drilled head, slotted fillister head screws are fabricated from steel meeting specification MIL-S-6050. Tensile strength 125,000 PSI. Cadmium plated, Type I, Class 3.

AN502 (FINE THREAD)

AN502 Dash No.*	Length (In.)	Thread Size	Price Each	AN502 Dash No.*	Length (In.)	Thread Size	Price Each
-10-5	5/16	10-32	.	-10-12	3/4	10-32	.
-10-6	3/8	10-32	.	-10-16	1	10-32	.
-10-8	1/2	10-32	.	-416-12	3/4	1/4-28	.
-10-10	5/8	10-32	.	-416-16	1	1/4-28	.

AN503 (COARSE THREAD)

AN503 Dash No.*	Length (In.)	Thread Size	Price Each	AN503 Dash No.*	Length (In.)	Thread Size	Price Each
-6-4	1/4	6-32	.	-10-6	3/8	10-24	.
-6-6	3/8	6-32	.	-10-8	1/2	10-24	.
-8-4	1/4	8-32	.	-10-10	5/8	10-24	.
-8-6	3/8	8-32	.	-10-12	3/4	10-24	.
-8-8	1/2	8-32	.	-10-16	1	10-24	.
-8-10	5/8	8-32	.	-10-24	1-1/2	10-24	.
-8-16	1	8-32	.	-416-8	1/2	1/4-20	.
				-416-10	5/8	1/4-20	.
				-416-12	3/4	1/4-20	.